

SURVEY N^o 1231

PT. ON OR NEAR
W¹/₄ POST SEC. 28

N 89° 37' E
210.60'

51.62'

ON OR NEAR
W. SEC. LINE

295.95'

30'

R/W LINE C.H. 97

N W PT SW¹/₄ SW¹/₄

6.158 A.

C. RICHARD
GOTTFRIED,
ET UX

34 1745 0000

NORTH 829.05'

30'

R.R. SPIKE SET
ON OR NEAR
SW COR SEC. 28

N 90° W
30'

N 84° 57' W
98.46'

S 60° 27' W
58.15'

S 88° 57' W
64.90'

S 66° 19' W
56.07'

S 42° 15' W
56.07'

S 20° 23' E
422.1'

S 3° 12' W 55° 42' E
116.82' 115.14'

S 17° 17' W
173.88'

S 30° 25' W
58.15'

S 60° 27' W
58.15'

S 88° 57' W
64.90'

S 66° 19' W
56.07'

S 42° 15' W
56.07'

U.S. 30 N.

SURVEY FOR RICHARD C.

SCALE 1" = 100'
● = R. R. SPIKE
○ = IRON PIPE
PT. SW¹/₄ SW¹/₄ SEC.
SALEM TOWNSHIP
WYANDOT COUNTY
DATE DECEMBER
BY J. B. WEININGER
OHIO REG. SURV.